

White Lightning®

WL2000 Drywall/All Purpose Construction Adhesive

Physical Properties:

Type:	Solvent Based Adhesive
Shelf Life:	18 months
Flash Point:	Less than 0°F
Open Time:	30 minutes
Dry Time:	24 hours
Application Temperature:	20°F to 110°F
Service Temperature:	0°F to 175°F
Storage Temperature:	Room Temperature
VOC Level:	344.3 g/l
Base:	Synthetic Rubber
Solids Content:	68%
Weight/Gallon:	9.2 lbs/gal
Color:	Tan
Consistency:	Medium Mastic

Performance Data:

Mildew Resistance:	Excellent
Water Resistance:	Excellent
Coverage:	Up to 39 linear ft./ctg @ 3/8" bead
Clean Up:	Mineral Spirits

Surface Preparation: Surfaces to be bonded must be clean, dry, and free of oil, grease and other contaminants.

Application: Place adhesive cartridge in hand caulking gun, cut nozzle, and puncture inner seal. Apply 3/8" adhesive bead to surface to be bonded. Press surface firmly in place.

Recommendations: Store adhesive at room temperature for at least 24 hours.

Walls: Nail at 16" intervals around perimeter of board where board contacts framing.

Ceilings: Where board contacts framing, nail at 16" intervals around perimeter. When board is installed parallel to framing, use four nails spaced 24" apart down the center of the board. When the board is installed across framing, use only one nail per framing member down the center of the board.

Specifications:

- Meets and exceeds ASTM C557
- Meets ASTM E72 for racking and shear
- Conforms to CAN/CG G-71.25-M88 (Canadian)
- Certified by BOCA under research Report #82-63
- Recommended by ICBO under Research #2231
- Accepted by HUD
- Meets FHA requirements

Packaging:

Color	Order #	UPC for Each	Size
Tan	WL21000	0-23275-30100-9	10.0 fl oz.
Tan	WL21100	0-23275-21100-1	29.0 fl. oz.