

White Lightning[®] Bolt[®] Quick Dry Adhesive Caulk

Physical Properties:

Type:	Adhesive Caulk
Color:	White
Shelf Life:	12 Months
Flash Point:	N/A Water Based
Flammability:	N/A Water Based
Cure Time:	5 to 7 days
Tack Free Time:	10 minutes
Application Temperature:	Above 50°F
Service Temperature:	-30°F to 180°F
VOC Level:	.898 lbs/gal
Mildew Resistance:	Good
Odor:	Low/None
Shrinkage:	Low/Moderate
Vehicle:	Water
Weight Solids:	76.3%
Weight/Gallon:	12.60 lbs

Performance Data:

Joint Movement Capability:	
Joint Size:	Between _" wide X _" deep and 1/8" X 1/8"
Freeze-Thaw Stability:	Passes through 5 cycles
Warranty:	40 Year Life
Clean Up:	Water
Flexibility:	Good
Surface Preparation:	Apply to a clean dry surface
Painting:	Paint within 30 minutes (with high quality paint)
Water Resistance:	Good
Cautions:	Do not take internally. Keep out of reach of children.

Specifications:

Passes flexibility, durability, and adhesion requirements of Fed. Spec. TT-S-00230C & ASTM Spec. C-920, Uses G & A.

Packaging

Size	Order #	UPC
10 oz Cartridge	WL20510	0-23275-20510-9
5.5 oz Squeeze Tube	WL20512	0-23275-20501-7

For more information please call or write:
White Lightning Products
101 Prospect Ave. NW
Cleveland, OH 44115
1-800-241-5295

