



Kitchen & Bath Latex Ultra Sealant

White Lightning® Kitchen & Bath Latex Ultra Sealant is a performance product formulated to seal and waterproof areas around bathtubs, basins, sinks, showers, toilets, countertops and splashboards. This unique formula delivers a high gloss finish similar to silicone.

- **HIGH GLOSS, BRIGHT WHITE FINISH**
- Paintable
- Water clean-up
- Combats the growth of mold, mildew and bacterial odors on cured sealant
- Interior or exterior use



Product Profile

Packaging:

Kitchen & Bath Latex Ultra Sealant	Color	Order #	UPC	Size
	White	WL0002510	0-23275-12861-3	10 FL OZ
	Clear	WL0002610	0-23275-12863-7	10 FL OZ
	Bisque	WL0002710	0-23275-12865-1	10 FL OZ
	White	WL0002515	0-23275-12862-0	5.5 FL OZ
	Clear	WL0002615	0-23275-12864-4	5.5 FL OZ
	Bisque	WL0002715	0-23275-12866-8	5.5 FL OZ



Indoor/Outdoor Use



Paintable



Water Clean-up



See opposite side for technical information

Kitchen & Bath Latex Ultra Sealant

Physical Properties: Kitchen & Bath Latex Ultra Sealant

Type:	Acrylic	Acrylic
Color:	White and Bisque	Clear
Shelf Life:	12 Months	12 Months
Flash Point:	n/a (water based)	n/a (water based)
Flammability:	n/a (water based)	n/a (water based)
Full Cure Time:	3 to 4 days	5 to 7 days
Tack Free Time:	45 Minutes at 75° F	45 Minutes at 75° F
Application Temperature:	40° F to 140° F	40° F to 140° F
Service Temperature:	-30° F to 180° F	-30° F to 180° F
VOC Level:	1.96%	
Mildew Resistance:	Excellent	Excellent
Water Resistance:	Excellent	Excellent
Odor:	Low	Low
Shrinkage:	Low	Low/Moderate
Vehicle:	Acrylic Polymer	Acrylic Polymer
Solids by Weight:	69+/-2%	62.02+/-1%
Weight/Gallon:	10.78+/-0.15	8.81+/-0.2 lb.
Painting:	Paintable	Paintable

Performance Data:

Joint Movement Capability:	Excellent	Excellent
Joint Size:	1/8" x 1/8" to 1/2" x 1/2"	1/8" x 1/8" to 1/2" x 1/2"
Freeze-Thaw Stability	Passes Through 5 Cycles	Stable Through 5 Cycles
Clean Up:	Water	Water
Flexibility:	Excellent	Excellent
Durability:	Excellent	Excellent

Product Description:

White Lightning® Kitchen and Bath Latex Ultra Sealant is an easy to use interior/exterior caulk. It is used for sealing and waterproofing areas around bathrooms, basins, sinks, showers, toilets, countertops and splashboards.

Surface Preparation:

Remove old caulk. Clean thoroughly to remove grease, dirt, oil, wax, loose paint, dust and soap film. Remove mildew with bleach and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

Painting:

A minimum of 4 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

Clean-Up:

Promptly clean tools and excess caulk with water or a damp cloth.

Cautions:

Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage.

Limitations:

For best results, apply at temperatures above 40° F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.



For more information please call or write:

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115
 1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com