

# White Lightning® Butyl Caulks

<u>Physical Properties:</u>	<u>Butyl Gutter &amp; Lap</u>	<u>Butyl Rubber Caulk</u>
Type:	Premium Sealant	Premium Sealant
Color:	Aluminum & Gray	White
Shelf Life:	12 months	12 months
Flash Point:	175°F	175° F
Flammability:	Unknown	Unknown
Cure Time:	24 to 48 hours	24 to 48 hours
Application Temperature:	Above 40°F	Above 40°F
Service Temperature:	-40°F to 180°F	-40°F to 180°F
Mildew Resistance:	Good	Good
Water Resistance:	Excellent	Excellent
Odor:	Solvent Like	Solvent Like
Shrinkage:	Low	Low
Vehicle:	Solvent Based	Solvent Based
Solids by Weight:	92%	92%
Weight/Gallon:	11.32 lbs./gal	11.32 lbs./gal
Painting:	Do not paint	Paintable

### Performance Data:

Joint Movement Capability:	Moderate	Moderate
Joint Size:	1/8" X 1/8" to _" X _"	1/8" X 1/8" to _" X _"
Freeze-Thaw Stability:	Stable through 5 cycles	Stable through 5 cycles
Clean Up:	Mineral Spirits	Mineral Spirits
Flexibility:	Excellent	Excellent

**Surface Preparation:** Surface should be free from oils, loose mortar, release agents, old caulking, old paint, or other contaminants.

**Cautions:** Contains aliphatic hydrocarbons and crystalline silica. Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

### Packaging:

Color	Order #	UPC	Size
<b>Butyl Gutter &amp; Lap</b>			
Aluminum	WL00116	0-23275-00116-9	10.0 fl oz
Gray	WL00115	0-23275-00115-2	10.0 fl oz.
<b>Butyl Rubber Caulk</b>			
White	WL00114	0-23275-00114-5	10.0 fl oz.

For more information please call or write:  
White Lightning Products  
101 Prospect Ave. NW  
Cleveland, OH 44115  
1-800-241-5295

