

White Lightning® Mortar Patch

Physical Properties:

Type:	Latex Caulk
Color:	Cement Gray
Shelf Life:	12 months
Flash Point:	N/A Water Based
Flammability:	N/A Water based
Cure Time:	7 to 14 days
Tack Free Time:	5 to 7 minutes
Application Temperature:	50°F to 120°F
Service Temperature:	-30°F to 180°F
Mildew Resistance:	Good
Water Resistance:	Good
Odor:	Low/None
Shrinkage:	Low/Moderate
Vehicle:	Water
Solids by Weight:	85%
Weight/Gallon:	15.7 lbs./gal

Performance Data:

Joint Movement Capability:	Moderate
Joint Size:	1/8" X 1/8" to _" X _"
Freeze-Thaw Stability:	Stable through 5 cycles
Clean Up:	Warm water
Flexibility:	Good

Surface Preparation: Surface should be free from oils, loose mortar, release agents, old caulking, old paint, or other contaminants

Painting: A minimum of 2 to 4 hours for dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

Cautions: Contains crystalline silica. Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage.

Packaging:

Color	Order #	UPC	Size
Cement Gray	WL70112	0-23275-70112-0	10.0 fl oz.

For more information please call or write:
White Lightning Products
101 Prospect Ave. NW
Cleveland, OH 44115
1-800-241-5295

