

White Lightning®

One Step Lightweight Spackling Compound

Physical Properties:

Type:	
Color:	White
Shelf Life:	12 Months
Flash Point:	N/A Water Based
Flammability:	N/A Water Based
Cure Time:	30 to 120 minutes
Application Temperature:	40°F and above
VOC Level:	0 lbs/gal
Mildew Resistance:	Good
Odor:	No odor
Shrinkage:	None
Vehicle:	Water
Weight Solids:	38.47%
Weight/Gallon:	4.09 lbs.

Performance Data:

Joint Movement Capability:	Not intended for moving joints
Freeze-Thaw Stability:	Passes through 5 cycles
Clean Up:	Easy water clean up
Flexibility:	Not intended for moving joints
Painting:	Paintable in 30 minutes
Surface Preparation:	Surface should be free from dust, dirt, or any loose contaminants.
Precautions:	Do not take internally; Keep out of reach of children; close container after each use. May irritate eyes. Immediately flush eyes with plenty of water for at least 10 minutes. Call physician.

Limitations:

Not for use on plastic or metal surfaces. Keep from freezing. Should not be applied where joint or other movement is expected. C-77 must be dry before painting. Normal dry time is 10 to 60 minutes, but can be up to 3 days for deep holes. Skim coating can lead to loss of adhesion, cracking, or paint alligatoring and is not recommended. Filling butt joints is also not recommended.

Packaging

Size	Order #	UPC
_ pint	WL60512	0-23275-60515-2
Pint	WL60517	0-23275-60517-6
Quart	WL60520	0-23275-60520-6

For more information please call or write:
White Lightning Products
101 Prospect Ave. NW
Cleveland, OH 44115
1-800-241-5295

