

White Lightning® Painter's Putty Multipurpose Patching Compound

Physical Properties:

Color:	Off White
Shelf Life:	12 months
Flash Point:	>200°F
Cure Time:	24 hours
Application Temperature:	Above 40°F
Water Resistance:	Good
Odor:	Slight
Shrinkage:	Low
Vehicle:	Linseed Oil
Weight/Gallon:	17.1 +/- 0.5 lb.
Clean Up:	Mineral Spirits

Surface Preparation: Surface should be clean, dry, and free from oils, dirt or other contaminants.

Painting: Allow 24 hours dry time before painting. Allow extra dry time during periods of high humidity and/or cool temperatures. Prime with an oil based primer before applying latex paint.

Application Directions:

1. Apply to a clean surface free from oils, dirt or other contaminants.
2. Prime all new or unpainted wood with an oil primer. Dull glossy areas by sanding lightly.
3. Open container and pour off protective layer of water. Dab excess moisture with a dry cloth.
IMPORTANT: When not in use, keep level in container and top off with a half inch of tap water to prevent putty from drying.
4. Soften putty by kneading or warming – DO NOT THIN
5. Shape and work putty into opening using a stiff putty knife.
6. Allow the surface to skin before sanding or painting. Skin will form within 24 hours. Prime with an oil-based primer before applying latex paint.
7. Clean hands and tools immediately after use with mineral spirits or soapy water.

Packaging:

Color	Order #	UPC for Each	Size
Off White	WL08115	0-23275-08115-4	_ Pint
Off White	WL08116	0-23275-08116-1	Quart

For more information please call or write:
White Lightning Products
101 Prospect Ave. NW
Cleveland, OH 44115
1-800-241-5295

