

White Lightning® Vinyl Spackling Compound

Physical Properties:

Type:	Vinyl
Color:	White
Shelf Life:	12 months
Flash Point:	>199°F
Flammability:	N/A Water Based
Cure Time:	24 hours
Tack Free Time:	12 minutes
Application Temperature:	Above 40°F
VOC Level:	.23 lb./gal
Odor:	Low/None
Shrinkage:	Minimal
Vehicle:	Water
Weight/Gallon:	14.7-15.1 lbs./gal

Performance Data:

Freeze-Thaw Stability:	Stable through 5 cycles
Clean Up:	Warm water
Resistance to Dirt Pick-up:	Good
Painting:	30 minutes

Application:

1. Apply to a clean, dry surface, free from dirt, dust, loose particles, and other contaminants.
2. Scrape or chisel out a crack or crevice bottom, making it wider than the top. This will anchor the White Lightning Vinyl Spackling Compound
3. Apply White Lightning Vinyl Spackling Compound directly from the container using a finger, putty knife, or broad knife wider than the hole to be patched. Smooth with as few strokes as possible. The putty or broad knife may be dipped in water for smoother finishing strokes. Trowel very large patches.
4. Fill in fine cracks by brushing on a water-thinned solution of White Lightning Vinyl Spackling Compound. For large holes or cracks, use two applications of White Lightning Vinyl Spackling Compound.
5. After the White Lightning Vinyl Spackling Compound dries, sand smooth if desired.
6. Let the area dry for 30 minutes before painting. Large holes or cracks may require longer drying times. It is always recommended to prime vinyl spackling before top coating with paint. Due to the porosity of some substrates, the entire surface to be painted may require primer for the most uniform appearance of the topcoat.
7. Clean up with water.

Packaging:

Color	Order #	UPC for Each	Size
White	WL060115	0-23275-60115-4	_ Pint
White	WL060117	0-23275-60117-8	Pint
White	WL060120	0-23275-60120-8	Quart

Specifications:

Meets requirements of Federal Specification SS-P-00450A, Type II

Precautions:

Contains Crystalline Silica. Use only with adequate ventilation. Avoid contact with eyes and skin. Do not take internally. Wash hands after using. Do not transfer contents to other containers for storage.

For more information please call or write:

White Lightning Products
101 Prospect Ave. NW
Cleveland, OH 44115
1-800-241-5295

