

**White Lightning®**  
**Window & Door**  
**Acrylic Latex Caulk with Silicone**

**Physical Properties:**

<b>Type:</b>	Acrylic Latex Caulk with Silicone
<b>Color:</b>	White
<b>Shelf Life:</b>	12 months
<b>Flash Point:</b>	N/A (Water based)
<b>Flammability:</b>	N/A (Water based)
<b>Cure Time:</b>	5 to 7 days at 75°F
<b>Tack Free Time:</b>	12 minutes at 75°F
<b>Application Temperature:</b>	50°F (10°C) and 120°F (49°C)
<b>Service Temperature:</b>	-30°F to 180°F
<b>VOC Level:</b>	.387 lbs./gal
<b>Mildew Resistance:</b>	Good
<b>Water Resistance:</b>	Good
<b>Odor:</b>	Low/None
<b>Shrinkage:</b>	Low
<b>Vehicle:</b>	Water
<b>Solids by Weight:</b>	82.6%
<b>Weight/Gallon:</b>	13.55 lbs.

**Performance Data:**

<b>Joint Movement Capability:</b>	Moderate
<b>Joint Size:</b>	_ " X _ " to 1/8" X 1/8"
<b>Freeze-Thaw Stability:</b>	Stable through 5 cycles
<b>Durability:</b>	35 Years
<b>Clean Up:</b>	Clean hands and tools easily with water
<b>Flexibility:</b>	Good

**Surface Preparation:** Surface must be dry and free of old caulk, dust, dirt, and grease

**Painting:** Paintable with latex or oil paints when dry, normally within 4-6 hours of application.

**Cautions:** Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

**Specifications:**

Exceeds ASTM Spec. C-834.

**Limitations:**

Do not use in butt joints or underwater. Do not use in areas subject to water immersion. Keep from freezing.

**Packaging:**

<b>Color</b>	<b>Order #</b>	<b>UPC</b>	<b>Size</b>
White	WL30600	0-23275-30600-4	10.0 fl oz.

For more information please call or write:  
White Lightning Products  
101 Prospect Ave. NW  
Cleveland, OH 44115  
1-800-241-5295

